

電氣規格書



Released Date:2018/11/22-05:29:25



全漢企業股份有限公司
FSP TECHNOLOGY INC.

台灣桃園市桃園區建國東路22號 統一編號：84239055
No. 22, Jianguo E. Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C)
TEL:+886-3-375-9888 Website:www.FSP-group.com
FAX:+886-3-375-6966 Email:sales@fsp-group.com.tw

SPECIFICATION

AC Adapter

FSP150-AAAN3

P.E	R/D	APPROVED	REV.
Zhiling Guo	Stephen Li	LJ Wei	02



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

History

REV.	Description	Date	Drawn	Mechanical	Electrical	Approved
00	SPEC ISSUE	Mar.17'17	Vivian	Zhiling Guo	Stephen Li	LJ Wei
01	Revise : 1.9 DOE(Level VI) 1.10 Erp(Tier 2) 4.8 Dielectric Strength	Sep.19'17	Vivian	Zhiling Guo	Stephen Li	LJ Wei
02	Revise : 4.5 EMI: Adapter comply with the following national standards	Dec.03'17	Vivian	Zhiling Guo	Stephen Li	LJ Wei

MODEL NO. **FSP150-AAAN3**

SHEET 1 OF 7



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

Electrical Requirements

1. Input Characteristics:

ITEM	CONDITION	SPECIFICATION
1.1 Rated Input Voltage:		100Vac~240Vac
1.2 Input Voltage Range:		90Vac to 264Vac
1.3 Input Frequency Range:		47Hz to 63Hz (± 1Hz)
1.4 Input Current:	100Vac, 240Vac / 6.25A load	≤ 2A
1.5 Input Current Harmonic:		IEC61000-3-2
1.6 Efficiency: (Warm up 10minutes later)	100Vac / 6.25A load 240Vac / 6.25A load	≥ 89% ≥ 91%
1.7 Power Saving:	115Vac, 230Vac / 10.4mA load(0.25W)	≤ 0.5W
1.8 Inrush Current:	100Vac, 240Vac / 6.25A load	Shall be less than the rating of adapter critical component (including rectifiers, fuse surge and current limiting device)
1.9 DOE(Level VI):	(1)115Vac / 0A load (2)115Vac / 25%,50%,75%,100% load (Average Active Mode Efficiency ,Warm up 30 minutes later)	≤ 0.21W ≥ 88% (DC Cable ≤ 1800 mm,18AWG)
1.10 Erp(Tier 2):	(1)230Vac / 0A load (2)230Vac / 25%,50%,75%,100% load (Average Active Mode Efficiency ,Warm up 30 minutes later)	≤ 0.15W ≥ 89% (DC Cable ≤ 1800 mm,18AWG)

MODEL NO. **FSP150-AAAN3**

SHEET 2 OF 7



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

2. Output Characteristics:

※Measured at the end of DC cable.

ITEM	CONDITION	SPECIFICATION
2.1 Output Rated Voltage:		24V
2.2 Output Current:	at constant voltage mode	0A to 6.25A
2.3 Output Voltage Setting:	at the output end of DC cable	24V \pm 5%
2.4 Output Voltage Ripple and Noise: (0.1uF Ceramic Cap. and 35V 47uF Aluminum Cap. Paralleled between the end of output cable)	100Vac, 240Vac / 0A~6.25A load	\leq 350mVp-p
2.5 Turn-On Delay Time:	At 100Vac / 6.25A load, output voltage shall remain regulation	\leq 3Sec
2.6 Hold Up Time:	At 100Vac or 240Vac / 6.25A load, output voltage shall remain regulation	\geq 10ms
2.7 Rise Time:	At 100Vac / 6.25A load, DC output rise time from 5% to 95% of Vo	\leq 50ms
2.8 Dynamic Load Change:	(1) Output load step is : 【1】 0 % ~50 % 【2】 50 %~100 % (2) S/R=0.5A/us (3) Frequency is 100Hz and 1KHz	24V \pm 10%
2.9 Overshoot:	100Vac, 240Vac / 0A and 6.25A load	24V \pm 10%

MODEL NO. **FSP150-AAAN3**

SHEET 3 OF 7



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

3. Protection Characteristics:

ITEM	CONDITION	SPECIFICATION
3.1 Short Circuit Protection:	When an internal fault occurs, or an external fault is applied to the power supply, such that an overload or short circuit is applied to the output, the power supply shall shut down and enter auto-recovery mode.	Shutdown and no damage
3.2 Over Voltage Protection:	The adapter will enter into shut down that means no output while over voltage happened at output terminal that caused by internal fault, the output trip voltage shall not exceed 37 volts. That will be return to normal state by AC reset.	Shutdown and no damage
3.3 Over Power Protection:	When an internal fault occurs, or an external fault is applied to the power supply, such that an overload or short circuit is applied to the output, the power supply shall shut down and enter auto-recovery mode.	Shutdown and no damage
3.4 Over Temperature Protection:	The power supply will enter into shut down while the abnormal thermal rise occurs. That will be return to normal state by AC reset.	No fire, no smoke

MODEL NO. **FSP150-AAAN3**

SHEET 4 OF 7



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

4. Environmental Characteristics:

ITEM	CONDITION	SPECIFICATION
4.1 Electric Fast Transients: Refer to IEC61000-4-4	Impulse: $\pm 1\text{kV}$ applied to L,N	Normal operation shall be continued
4.2 Lightning Surge: Refer to IEC61000-4-5	$\pm 1\text{kV}$ applied differential mode $\pm 2\text{kV}$ applied common mode	Normal operation shall be continued Normal operation shall be continued
4.3 Electron Static Discharge: (Refer to IEC61000-4-2 Energy Storage Capacitor 150pF; Discharge Resistor 330 Ω)	Air Discharge: $\pm 15\text{KV}$ Contact Discharge: $\pm 8\text{KV}$	Normal operation shall be continued
4.4 Cooling:	Natural air cooling	
4.5 EMI: Adapter comply with the following national standards: EMI Conducted Emission EMI Radiated Emission	1.Full Load 2. The power supply with internal filter can meet.	FCC PART 15B CLASS B CISPR32 EN55032 CLASS B VCCI LEVEL II
4.6 Safety conforming: 4.6.1 Energy-related Products 【ErP】 Department of Energy 【DOE】		Regulated by customer Comply with ErP standard Comply with DOE standard
4.7 Leakage Current:	264Vac / 50Hz	$\leq 0.25\text{mA}$
4.8 Dielectric Strength: (Hi-Pot)	Between AC input and secondary applied DC 4242V / test time 1 minute / cut off current shall be less than 10mA	
4.9 Temperature:	Operating Storage	0 to 40°C -20 to +80°C
4.10 Humidity:	Operating Storage	20% ~ 80% 10% ~ 90%

MODEL NO. **FSP150-AAAN3**

SHEET 5 OF 7



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

5. Mechanical Characteristics:

ITEM	CONDITION	SPECIFICATION
5.1 Dimension (Length x Width x Height):		151.3 X 75.6 X 25.4 mm
5.2 Adapter weight:		485g(typical)
5.3 Input AC socket Type:		IEC 320-C14 Type
5.4 Vibration Test:	(1) Non-operating, 0.01g ² /Hz at 5Hz slopping to 0.02g ² /Hz at 20Hz, And maintain 0.02g ² /Hz from 20Hz ~ 500Hz (2) PSD=3.13grms, 15 minutes/axis (3) Vibration duration:15minutes (4) Vibration waveform:Random (5) Force Direction X,Y,Z	Normal operation shall be continued.
5.5 Acoustic Noise:	(1) Position the microphone 30 centimeters above the x-y center of the AC adapter (2) Input voltage:110Vac/60Hz 220Vac/50Hz	The EUT < 30dB

MODEL NO. **FSP150-AAAN3**


SHEET 6 OF 7



全漢企業股份有限公司
FSP TECHNOLOGY INC.

Electrical Specification

Note : Acoustic Noise



MODEL NO. **FSP150-AAAN3**

SHEET 7 OF 7